

SIZE CHART AND COLONIAL LITE CONFIGURATIONS

					COMMODITY				MODULAR			
WINDOW WIDTH	19 1/8	26 1/2	37	53 1/8	24	32	40	44	48			
MASONRY OPENING	19 7/8	27 1/4	37 3/4	53 7/8	24 3/4	32 3/4	40 3/4	44 3/4	48 3/4			
WOOD FRAME OPENING	18 5/8	26	36 1/2	52 5/8	23 1/2	31 1/2	39 1/2	43 1/2	47 1/2			
ALUMINUM FRAME OPENING	18 1/4	25 5/8	36 1/8	52 1/4	23 1/8	31 1/8	39 1/8	43 1/8	47 1/8			
26	26	25 1/2	25 1/8	NA								
38 3/8	38 3/8	37 7/8	37 1/2	*13 1/16								
50 5/8	50 5/8	50 1/8	49 3/4	*19 1/4								
63	63	62 1/2	62 1/8	*19 1/4								
76	76	75 1/2	75 1/8	*25 3/8								
WINDOW HEIGHT	MASONRY OPENING	WOOD FRAME OPENING	ALUMINUM FRAME OPENING	PRO-VIEW (NON-COLONIAL) SASH HEIGHT								

MINIMUM & MAXIMUM SIZES	
MINIMUM	MAXIMUM
1/1 12 x 23	53 1/8 x 76

Note: Masonry openings given assume a precast sill and a 1x buck. If using poured sill, add 3/4". Framing dimensions are calculated with drywall butted against window frame.

*Sash heights are different sizes on colonial Pro-views.